

# 20 FLOOR FINISH



## DESCRIPTION

This is a metal, crosslinked floor finish especially designed for high speed buffing, which exhibits a remarkable gloss, both initially and after buffing with a noticeable resistance to scuffing and black heel marks.

## DIRECTIONS

**PREPARATION OF FLOOR:** Follow recommended dilution of stripper. Strip floor thoroughly of old wax or floor finish. For heavy buildup areas, such as baseboards, under desks, etc., you may have to apply more stripper to the floor as the stripper solution becomes diluted with old loosened finish. Rinse the floor as thoroughly as possible with clear water and allow to dry.

**APPLICATION OF FINISH:** Work with clean equipment. Before use, soak mops in water and wring out tightly, so they absorb less finish and are easier to clean. Apply finish in uniform light to medium coats. Coat traffic lanes more than other areas and work additional coats toward the edges. Recommended application for every three coats in traffic areas apply one coat to non-traffic areas.

**CLEANING/MAINTENANCE:** Daily sweeping and dust mopping is critical for any floor care program. Damp mopping a neutral cleaner and following the recommended dilutions of the product as required are also needed. Before spray buffing or high burnishing the floor needs to be cleaned with either of the previous directions.

## APPLICATIONS

### Product for Use on Floors in:

- >Schools and Institutions
- >Office Buildings
- >Hospitals

## SPECIFICATIONS

Color .....	White
Fragrance .....	Characteristic
pH Range.....	8.0-8.5
Dilution.....	RTU
Density.....	8.67

## PACKAGING

### ITEM#.....SIZE

700041-41.....	4/1 Gal.
700041-55.....	55 Gal.