

# FLOOR & CONCRETE SEALER



## DESCRIPTION

A glossy, tough sealer for renovating worn asphalt tile, rubber tile, and linoleum tile as well as concrete, brick, terrazzo, and other masonry surfaces.

## DIRECTIONS

### DIRECTIONS FOR WORN FLOORS

- Thoroughly remove all traces of accumulated wax, using a good wax stripper in accordance with manufacturers recommendations. Rinse floor and allow it to dry.
- When floor has dried, apply an even coat of **Wepak Floor & Concrete Sealer** using a lamb's wool applicator or a clean mop.
- If first coat does not show an even surface gloss this indicates that the floor is extremely worn and porous. In this case, apply a second coat after the first coat has dried for at least 30 minutes.
- Floor is now prepared for normal application of quality, self polishing or polymer finish. Apply one coat after **Wepak Floor & Concrete Sealer** has dried for one hour.
- Maintain floor as usual. This sealer treatment will last through multiple strippings of the top coat. Repeat the above application only when loss of gloss becomes severe.

### DIRECTIONS FOR UNDERCOATING NEW FLOORS

- Thoroughly remove all traces of previous waxes or tile manufacturer's protective coating by using a good wax stripper. Rinse well, and allow floor to dry. (**NOTE:** On newly laid floors allow one week for mastic to set.)
- When floor is thoroughly dry, apply one coat of **Wepak Floor & Concrete Sealer** with a lamb's wool applicator or a clean mop. Allow floor to dry for one hour.
- Apply one coat of your favorite wax or polymer finish and maintain as usual.

No warranty, express or implied, or merchantability, fitness or otherwise is made.

## APPLICATIONS

### Product for Use on:

- >Concrete and Asphalt
- >Rubber Tile and Linoleum
- >Brick and Terrazzo

## SPECIFICATIONS

Color .....	White
Fragrance .....	Bland
pH Range.....	7.5-9.0
Dilution.....	RTU
Density.....	8.59

## PACKAGING

ITEM#.....	SIZE
700070-41.....	4/1 Gal.
700070-05.....	5 Gal.